

Flatback Paper Tape

267

1464

page 1 of 3

Technical Data

September 1, 1998

Supersedes November 1, 1997

Product Description A flatback paper tape for color coding, bundling and bag sealing. It is easy to write on and is printable by many flexographic processes.

Product Construction Backing: Flat stock paper
Adhesive: Rubber
Color: Red, white
Standard Roll Length: 60 yds. (54.8m)

Typical Physical Properties **Note:** The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM TEST METHOD
Adhesion to Steel:	30 oz./in. width (33 N/100mm)	D-3330
Tensile Strength:	25 lbs./in. width (438 N/100mm)	D-3759
Elongation at Break:	5%	D-3759
Tape Thickness:	5.8 mils (0.15mm)	D-3652
Temperature Use Range:	Up to 200°F (93°C) for 60 minutes	

- General Information**
1. Holds well to a variety of paper, film, fabric and yarn surfaces.
 2. Tape 267 is printable with most standard flexographic inks and is also easily marked with ballpoint pens, felt-tip pens, pencils and rubber stamps.
 3. Its heat resistance will generally allow it to function during bake cycles of up to 200°F (93°C) for up to one hour.
 4. Tape 267 should not be subjected to outdoor exposure or prolonged periods of exposure to sunlight. Tape may become very difficult to remove.
 5. Tape 267 is manufactured in an ISO 9002 registered plant to meet worldwide quality standards.

Shelf Life To obtain best performance, use this product within one year from date of manufacture and store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.

Application Ideas

1. Tape 267 can be used for a wide variety of bundling, banding, sealing, tabbing, defect flagging and holding applications where color for identification or coding is desired.
2. Light to medium bundling applications.
3. Banding items where color coding is required.
4. Last lap end roll tabbing of paper, film, fabric and yarns.

Features

<u>FEATURES</u>	<u>ADVANTAGES</u>	<u>BENEFITS</u>
Rubber adhesive	Instant adhesion	Sticks easily/helps reduce labor
	Good holding power	Resists lifting or curling
Colored paper backing	Clean removal from a variety of surfaces	Helps reduce clean-up
	Easy tear	Good handling/helps reduce rework
	Bright colors	Easy identification
	Two colors	Variety in coding
Exclusive backsize treatment	Controlled unwind	Easy to use/helps reduce waste
	Printability	Easily marked with pens, pencils and stamp markings

Technical Data

All physical properties, statements, and recommendations are either based on tests we believe to be reliable or our experience, but they are not guaranteed. 3M recommends each user determine the suitability of the masking paper, film or tape for the intended use.

Important Notice

3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of application. Please remember that many factors can affect the use and performance of a 3M ITSD product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M ITSD product. Given the variety of factors that can affect the use and performance of a 3M ITSD product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M ITSD product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Limitation of Remedies and Liability

If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for any loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.



Industrial Tape and Specialties Division

3M Center, Building 220-7W-03
St. Paul, MN 55144-1000
USA
1 800.722.5463
651.733.9017 FAX
1 800.223.7427 Fax On Demand
<http://www.3M.com>

3M Canada Inc.

PO Box 5757
London, Ontario
Canada N6A 4T1
519.451.2500
519.452.6262 FAX

3M Europe

Hermeslaan 7
B – 1831 Diegem
Belgium
32 (0)2 722.45.50
32 (0)2 722.45.18 FAX

3M do Brasil Ltda – Cepi 23050

Caixa Postal 123
Campinas – SP – Brazil
Cep. 13001-970
55 19 864.7143
55 19 864.7637 FAX

3M Mexico, S.A. de C.V.

Av. Santa Fe No. 55
Col. Santa Fe, Del. Avaro Obregón
México D.F. 01210
52 5 270.0400
52 5 270.2299 FAX

3M Puerto Rico, Inc.

Puerto Rico Industrial Park
PO Box 100
Carolina, PR 00986-0100
787.750.3000
787.750.3035 FAX

3M Asia Pacific Pte. Ltd.

9, Tagore Lane
Singapore 787472
Republic of Singapore
65 454.8611
65 456.8953 FAX