

# Highland<sup>TM</sup>

## Colored Cloth Duct Tape

### 6969

**1428**  
page 1 of 3

---

#### Technical Data

**September 1, 1998**

Supersedes March 1, 1998

---

**Product Description** General purpose polyethylene coated cloth duct tape. Available in five colors for color coding, sealing, holding, protecting from moisture, temporary repairs and general maintenance activities.

---

**Product Construction** Backing: Polyethylene coated cloth  
Adhesive: Rubber  
Color: Black, white, red, olive green, silver  
Standard Roll Length: 60 yds. (54.8m)

---

#### Typical Physical Properties

**Note:** The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		<b>ASTM TEST METHOD</b>
Adhesion to Steel:	51-58 oz./in. width (56-63 N/100mm)	D-3330
Tensile Strength:	22-29 lbs./in. width (384-506 N/100mm)	D-3759
Elongation at Break:	13-23%	D-3759
Tape Thickness:	9.9-10.5 mils (0.25-0.27mm)	D-3652
Temperature Use Range:	Up to 200°F (93°C) for up to 1 hour	

---

#### General Information

1. The aggressive and high tack adhesive of 6969 tape allows it to adhere readily and tightly to a variety of surfaces.
  2. Tape 6969 uses a cloth backing that is conformable and easy to tear by hand.
  3. Five colors of 6969 tape are available for color coding and identification purposes.
  4. Typically used at room temperature, but will hold on to a steel surface up to 200°F (93°C) for one hour.
-

# Highland™ Colored Cloth Duct Tape

6969

1428

page 2 of 3

---

**Shelf Life** To obtain best performance, use this product within one year from date of manufacture and store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.

---

**Application Ideas** Sealing heating, ventilation and air conditioning ducts. Protecting surfaces and openings from dust, dirt and moisture. Color coding for easy identification. Making temporary repairs. Wrapping and bundling. General maintenance activities.

---

<b>Features</b>	<b><u>FEATURES</u></b>	<b><u>ADVANTAGES</u></b>	<b><u>BENEFITS</u></b>
	Polyethylene coated cloth backing	Resists moisture	Prolongs tape bond
		Conformable	Can be used on many irregular surfaces
		Hand tears easily	Ease of application
		Good tensile strength	Strong for tough applications
	Five backing colors	Color coding	Easy identification
	Adhesive	High tack	Provides good seal
		Good holding power	Stays where you put it
		Adheres aggressively to a variety of surfaces	Useful for many general purposes

---

**Technical Data** All physical properties, statements, and recommendations are either based on tests we believe to be reliable or our experience, but they are not guaranteed. Minnesota Mining and Manufacturing recommends each user determine the suitability of the masking paper, film or tape for the intended use.

---

---

## Important Notice

MINNESOTA MINING AND MANUFACTURING (MANUFACTURER) MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the MANUFACTURER's product is fit for a particular purpose and suitable for user's method of application. Please remember that many factors can affect the use and performance of a MANUFACTURER's product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a MANUFACTURER's product. Given the variety of factors that can affect the use and performance of a MANUFACTURER's product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the MANUFACTURER's product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

---

## Limitation of Remedies and Liability

If the MANUFACTURER's product is proved to be defective, THE EXCLUSIVE REMEDY, AT THE MANUFACTURER's OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE MANUFACTURER's PRODUCT. The MANUFACTURER shall not otherwise be liable for any loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

### United States

St. Paul, MN 55144-1000  
USA  
1 800.722.5463  
651.733.9017 FAX  
1 800.223.7427 Fax On Demand

### Canada

PO Box 5757  
London, Ontario  
Canada N6A 4T1  
519.451.2500  
519.452.6262 FAX

### Brasil Ltda – Cepi 23050

Caixa Postal 123  
Campinas – SP – Brazil  
Cep. 13001-970  
55 19 864.7000  
55 19 864.1206 FAX

### Puerto Rico

PO Box 100  
Carolina, PR 00986-0100  
787.750.3000  
787.750.3035 FAX

### Europe

Hermeslaan 7  
B – 1831 Diegem  
Belgium  
32 (0)2 722.45.50  
32 (0)2 722.45.18 FAX

### Mexico, S.A. de C.V.

Av. Santa Fe No. 55  
Col. Santa Fe, Del. Avaro Obregón  
México D.F. 01210  
52 5 270.0400  
52 5 270.2299 FAX

### Asia Pacific Pte. Ltd.

9, Tagore Lane  
Singapore 787472  
Republic of Singapore  
65 454.8611  
65 456.8953 FAX